

FIG.1




FIG.2




FIG.3A




FIG.3B




FIG.3C




FIG.4




FIG.5




FIG. 6

SET VALUE INPUT

301

	AREA 1	AREA 2	AREA 3
BOLTZMANN'S CONSTANT σ	5.67E-08		
HEAT TRANSFER COEFFICIENT α	2.50E-01	2.50E-01	2.50E-01
EMISSIVITY OF BOARD Emk	9.00E-01		
EMISSIVITY OF PARTS Emb	9.50E-01		
BOARD AREA S1	1.00E-01		
PARTS AREA S2	1.60E-03		
HEAT CAPACITY OF BOARD Ck	1.86E+02		
HEAT CAPACITY OF PARTS Cb	5.95E+00		
VIEW FACTOR OF BOARD Fk	—	—	—
VIEW FACTOR OF PARTS Fb	—	—	—
HEATER TEMPERATURE Th	423	0	588
BLOWER TEMPERATURE Tg	413	433	483


ANALYSIS RESULTS

	AFTER 41 SECONDS	AFTER 130 SECONDS	AFTER 171 SECONDS
BOARD TEMPERATURE Tk	108.6	131.32	197.3
PARTS TEMPERATURE Ttb	97.0	125.4	176.1
TEMPERATURE DIFFERENCE BETWEEN BOARD AND PARTS	11.61	5.95	21.21

302

BOARD $f(t, Tk(t)) = k_1 \cdot (Th^4 - Tk(t)^4) + k_2 \cdot (Tg - Tk(t))$
 $k_1 = \sigma \cdot (S1 - S2) \cdot Emk \cdot F / Ck$ $k_2 = \alpha \cdot (S1 - S2) / Ck$

PARTS $f(t, Tb(t)) = k_1 \cdot (Th^4 - Tb(t)^4) + k_2 \cdot (Tg - Tb(t))$
 $k_1 = \sigma \cdot S2 \cdot Emb \cdot F / Cb$ $k_2 = \alpha \cdot S2 / Cb$



303

FIG.7




FIG.8




FIG.9

SET VALUE INPUT 501

	AREA 1	AREA 2	AREA 3
BOLTZMANN'S CONSTANT σ	5.67E-08		
HEAT TRANSFER COEFFICIENT α	2.50E-01	2.50E-01	2.50E-01
EMISSIVITY OF BOARD Emk	9.00E-01		
EMISSIVITY OF PARTS Emb	9.50E-01		
BOARD AREA S1	1.00E-01		
PARTS AREA S2	1.60E-03		
HEAT CAPACITY OF BOARD Ck	1.86E+02		
HEAT CAPACITY OF PARTS Cb	5.95E+00		
VIEW FACTOR OF BOARD Fk	—	—	—
VIEW FACTOR OF PARTS Fb	—	—	—


	AFTER 41 SECONDS	AFTER 130 SECONDS	AFTER 171 SECONDS
BOARD TEMPERATURE Tk	88.7	120.27	191.9
PARTS TEMPERATURE Ttb	70.3	110.7	191.9
TEMPERATURE DIFFERENCE BETWEEN BOARD AND PARTS	18.46	9.58	0.00

CALCULATION RESULTS

	AREA 1	AREA 2	AREA 3
HEATER TEMPERATURE Th	423	0	773.20108
BLOWER TEMPERATURE Tg	413	433	240.17363

BOARD $f(t, Tk(t)) = k_1 \cdot (Th^4 - Tk(t)^4) + k_2 \cdot (Tg - Tk(t))$
 $k_1 = \sigma \cdot (S1 - S2) \cdot Emk \cdot F / Ck$ $k_2 = \alpha \cdot (S1 - S2) / Ck$

PARTS $f(t, Tb(t)) = k_1 \cdot (Th^4 - Tb(t)^4) + k_2 \cdot (Tg - Tb(t))$
 $k_1 = \sigma \cdot S2 \cdot Emb \cdot F / Cb$ $k_2 = \alpha \cdot S2 / Cb$



503

502

FIG.10




FIG.11A




FIG.11B

